LADDER INSPECTION CHECKLIST

Refer to the following inspection criteria when assessing each ladder <u>prior</u> to use.

By signing (initialing) and dating the inspection tag affixed to any ladder, you are attesting that the ladder is in good condition and acceptable for use in accordance with the checklist below.

		YES	NO	NA
1	Steps, rungs & endcaps are undamaged and free from grease, dirt, or slick substances			
2	Rails are undamaged and free from grease, dirt, or slick substances			
3	Top shelf or platform is undamaged and free from grease, dirt or slick substances			
4	All hardware and fittings are secure (e.g. screws, bolts, hinges, etc.)			
5	Ladder is free from any sharp surfaces, splinters or burrs (e.g. on rails, steps, rungs)			
6	Instruction and warning labels are not missing, and are legible			
7	All moveable parts operate properly and smoothly			
8	Pail shelf is not missing, bent or broken			
9	Ladder is fully stable when resting on an even dry surface (e.g. no wobbling)			
10	Spreaders, bracing and/or extension locks are undamaged and work properly			
11	Pulley and ropes are undamaged/un-frayed and work properly			
12	Rung locks are in place and none are missing or broken			
13	Slip resistant shoes and feet are undamaged and work properly			
14	Ladder does not have rust, corrosion, loose/missing pieces or decay			

If you answer 'NO' to any of the inspection criteria above, place the ladder 'OUT OF SERVICE' by tagging it appropriately and have it repaired or replaced, as necessary.

LADDER IS IN GOOD CONDITION & ACCEPTABLE FOR USE

YES

NO 🗆

Always follow ladder manufacturer instructions and comply with applicable state and federal OSHA standards.

For replacement tags or if a ladder is placed out of service, contact EH&S at X5817.